

5020H24B (50*50*20) 散热风扇



轴承结构: 含油轴承 ; 滚珠轴承
Bearing system: Sleeve Bearing; Dual Ball Bearing;
框叶材质: PBT 环保防火
Frame Material: PBT Environmental Fire Protection;
电压范围: 5~24V
Voltage range: 5~24V
工作温度: -10℃~+70℃
Operating temperature: -10℃~+70℃

*以下功能部份可选择 (The following features are optional)

马达保护 (Motor protection)		
反向保护 (Reverse protection)	过温保护 (Over-temperature protection)	
信号输出 (Signal output)		
转速信号 (FG)	报警功能 (RD)	
调速方式 (Speed control mode)		
脉宽调速 (PWM)	电压调速 (Voltage speed)	温控调速 (Tt)

温馨提示: 网页数据仅供参考, 若有特殊需求, 请直接与业务人员联络, 谢谢!

SPECIFICATIONS (产品规格)

Model	Voltage (VDC)	Current (Amp)	Power (Watts)	Speed (RPM)	Air Flow (CFM)	Pressure (mmH2O)	Noise Level (dBA)
5020H24B	24	0.15	3.60	6500	20.20	7.11	39.20
5020M24B	24	0.10	2.40	5500	15.51	4.57	33.00
5020L24B	24	0.08	1.92	4500	12.35	2.54	26.00
5020H12B	12	0.20	2.40	5500	15.51	4.57	33.00
5020M12B	12	0.5	1.80	4500	12.35	2.54	26.00
5020L12B	12	0.09	1.08	3500	9.61	1.98	20.22
5020H05B	5	0.32	1.60	5500	15.51	4.54	33.00
5020M05B	5	0.26	1.30	4500	12.35	2.54	26.00
5020L05B	5	0.18	0.90	3500	9.61	1.98	20.22

